

Porsche 911 GT3 RS (991)

Product Name: Evolution Header Set (Titanium) RS Product code: E-PO/T/4 Approval: W/O

MSRP ex. VAT: 7.170,05 €





INFO

Evolution Header Set converts the slip-on system into a full Evolution Line system designed to give noticeably increased power at higher revs. With superb attention to detail, including parts cast in Akrapovič's own titanium foundry, the craftsmanship and coating finish on the system is a joy to behold. With a newly developed exhaust manifold, incorporating 100 cpsi sports catalytic convertors and side mufflers—all designed to increase power and torque—the Evolution Line utilizes integrated catalytic convertors and the functionality of the new exhaust valves to deliver an out-and-out attack on the senses. With the valves in the open position, the Evolution Line sounds like the top-performing Evolution Race system, but also has the option of a lower sound level when the valves are closed, perfect for use in more everyday locations. Offering an increased weight savings in the area behind the engine and the rear axle, the reduction will enhance the handling and improve performance. The Evolution Line is also tuned to deliver a sportier and hard-hitting sound—in open valve mode, the more the engine is revved the better the sound gets—as well as increasing performance, all to provide an even greater sensory experience.

When installing Akrapovič aftermarket optional link pipes with sports catalytic converters or without catalytic converters, which are developed for use on closed tracks only, remapping the ECU is mandatory. When installing Akrapovič aftermarket exhaust system that was developed for use on closed tracks, we recommend remapping the ECU in order to prevent potential »check engine light« warning signals.

THIS PRODUCT DOES NOT MEET EMISSION COMPLIANCE REQUIREMENTS FOR STREET OR HIGHWAY USE.



Porsche 911 GT3 RS (991)

Product Name:Evolution Header Set (Titanium) RSProduct code:E-PO/T/4Approval:W/0

TECHNICAL DATA

	UNIT	STOCK	AKRAPOVIČ	MAX GAIN
maximum power	kW	345.7 / 8450 rpm	351.2 / 8400 rpm	+ 10.0 / 8000 rpm
	HP(m)	470.0 / 8450 rpm	477.5 / 8400 rpm	+ 13.6 / 8000 rpm
	HP(i)	463.6 / 8450 rpm	471.0 / 8400 rpm	+ 13.4 / 8000 rpm
maximum torque	Nm	426.2 / 3850 rpm	437.4 / 6350 rpm	+ 27.3 / 3850 rpm
	lb-ft	314.3 / 6450 rpm	322.6 / 6350 rpm	+ 20.1 / 3850 rpm
weight	kg	38.9	24.8	- 14.1
	lb	85.8	54.7	- 31.1
	%			- 36.2
installation time	min		200	